



TOUCHLESS CAR & MOTORCYCLE DRYER



FILTERED HEATED AIR



PREVENTS WATER SPOTTING



ELIMINATES SCRATCHING
AND STREAKING



DOES NOT REMOVE WAX



PREVENTS RUST

CHOOSE YOUR *BLOW^R*

BLOW^R MINI



3000 watts' single motor



2 stage wind control



Filtered heated air



Working temperature
from 15C - 45C



Noise reduction system



35 x 40 x 20 cm



BLOW^R PRO



2800 watts' twin motor



4 stage wind control



Filtered heated air



Fixed. 20° C higher than
the surrounding environment



Noise reduction system



45 x 40 x 20 cm



**DRIES
80%
FASTER**



BLOW^R MINI

Extra long 3.5 meter
Commercial Grade Hose

Neoprene Rubber
Blower Nozzle

Low Noise reduction
technology with single
filter system

BTT (Bigboi Temperature Technology)
3 stage adjustable warm filtered
air 15° C / 25° C / 45° C higher than
the surrounding environment

adjustable
wind control

2 stage adjustable wind control
achieving wind speeds
up to 200 km/h

The most efficient twin single
system in the industry
consisting of 3000 watts
(over 4 HP)

Safe hose locking system.
No need for messy external clamps.

E/Z changeable foam
filter (wash and re-use),
allowing warm safe filtered
air to pass onto the paintwork.



Working temperature
from 15C - 45C



The most efficient motor
system in the industry



E/Z change foam filter
using warm filtered air



Low Noise
reduction technology



Adjustable wind control
achieving wind speeds
up to 200 km/h